

## Writeboard – “Paint on Whiteboard Coating”

**PRODUCT DESCRIPTION:** A & I Coatings Writeboard paint is a water borne two pack clear polyurethane coating which provides an exceptional surface for writing on with white board markers. Features of this product include ease of white board marker removal, user friendly application properties and a low odour, water based composition.

### TYPICAL APPLICATIONS:

- Schools
- Offices
- Playrooms
- Virtually any primed surface you would like to write on.

### TECHNICAL INFORMATION

**Mixing Ratio** : 2:1 (Pack A : Pack B) by Volume.

**Pot life** : 1.5 - 2 hours@25°C

**Finish** : Gloss

**Colour** : Clear

**Dry time (minimum)** : Touch dry 30mins @25°C  
Full cure 7 days @25°C  
Allow 3 full days for the coating to cure before writing on your Writeboard surface

**Primer Required** : Writeboard paint must always be applied over a water based acrylic basecoat

**Coverage** : 9m<sup>2</sup>/L – premeasure the amount of wall space the kit is intended to cover and ensure the entire content of the kit is used for that area. Spreading the paint too thin will result in poor marker removal properties

**Usual no. of coats** : 1

**Dry Film Thickness** : 40 microns

**VOC Content** : 41grams/Litre

## **APPLICATION DATA**

### **Please view the instructional DVD prior to commencing**

- Mixing** : Hand stir Pack A with Pack B thoroughly for a minimum of 3 minutes,
- Equipment** : Use the equipment supplied if using a 450ml kit size. For larger kit sizes which aren't supplied with the application equipment, use a 14mm nap microfiber roller. Other items required include a paint tray, drop sheets, stirrer, gloves and 400 grit sandpaper.
- Application** : Writeboard Paint must be applied over a low sheen water based acrylic coating. Always apply Writeboard paint within 7 days of the acrylic being applied. If applying the Writeboard Paint after 7 days of the acrylic being supplied lightly sand the acrylic using 400 grit sandpaper. Take care not to over sand the surface as sanding marks may then be seen through the Writeboard Paint. Apply the Writeboard Paint in one even coat ensuring a wet, even finish is achieved with no misses. This product is water clean-up.

## **PACKING & STORAGE**

- Packing** : Available in 450mL or 4.5L packs. For availability of other sizes, contact **A & I Coatings**.
- Storage** : 12 months if stored in sealed containers away from heat and moisture. Subject to re-inspection thereafter.

**HEALTH AND SAFETY** : All applicable statutory regulations must be observed in the application of this product. Users must first read the Safety Data Sheet for Writeboard Paint. Users should familiarise themselves with all the safety aspects of the product prior to usage.

Please ensure the current Technical Data Sheet is consulted prior to specification or application of **A & I Coatings** products.

All surplus materials and empty containers should be disposed of in accordance with appropriate regional regulations/legislation.

*Note: The figures quoted for pot life and drying/curing times are not definitive. They are dependent on site conditions, such as volume of material mixed, ambient and substrate temperatures, weather and ventilation.*

## **DISCLAIMER**

*Since the use and application of this product is beyond our control we cannot be held responsible for product field performance. The information presented above is the result of our considerable experience with this product but is not to be construed as a performance warranty.*



For additional information, phone our Customer Service Centre on 1800 819 585, or e-mail [helpdesk@aicoatings.com](mailto:helpdesk@aicoatings.com)  
Visit our website for more products: [www.aicoatings.com](http://www.aicoatings.com)

April 2018 - THIS DATA SHEET SUPERSEDES THOSE PREVIOUSLY ISSUED.